

SmartLogger3000A



	SmartLogger3000A03EU	SmartLogger3000A01EU
	80	
	Communication Interface	
WAN	WAN x 1, 10 / 100 / 1000 Mbps	
LAN	LAN x 1, 10 / 100 / 1000 Mbps	
RS485	COM x 3, 1200 / 2400 / 4800 / 9600 / 19200 / 115200 bps, 1000 m	
MBUS	MBUS x 1, 115.2 kbps,	PLC MBUS
2G / 3G / 4G ¹	LTE(FDD) : B1,B2,B3,B4,B5,B7,B8,B20 DC-HSPA+/HSPA+/HSPA/UMTS : 850/900/1900/2100 MHz GSM/GPRS/EDGE: 850/900/1800/1900 MHz ²	
/ /	DI x 4, DO x 2, AI x 4	
	12V, 100mA (' ,)	
Ethernet	Modbus-TCP, IEC 60870-5-104	
RS485	Modbus-RTU, IEC 60870-5-103 (,) , DL / T645	
LED	LED	x 3 – RUN, ALM, 4G
WEB	Web	
USB	USB 2.0 x 1	
APP	WLAN	
	-40°C ~ 60°C (-40°F ~ 140°F)	
	-40°C ~ 70°C (-40°F ~ 158°F)	
	5% ~ 95%	
	4,000 m (13,123 ft.)	
	100 V ~ 240 V, 50 Hz / 60 Hz	
	12 V / 24 V	
	8 W, . 15 W	
(W x H x D)	225 x 160 x 44 mm (8.9 x 6.3 x 1.7 inch, without mounting ears and antenna)	
	2 kg (4.4 lb.)	
	IP20	
	, DIN- ,	

*1:
*2: